



Standard Inverter- CS/CU-PU12XKJ

Model

(50Hz)	CS-PU12XKJ (CU-PU12XKJ)
--------	----------------------------

Kapasitas Pendinginan

(min-max)	kW	3,50 (0,92-3,80)
	Btu/h	11.900 (3.140-13.000)

EER (rated)

(min-max)	12,53 (11,30-14,27)
-----------	---------------------

EER (label)

Btu/hW	13,70
--------	-------

Tingkat Bintang

Star Level	Bintang 4
------------	-----------

Data kelistrikan

Voltase	V	220
Arus Daya	A	4,4
Daya Listrik (min-max)	W	950 (220-1.150)

Penghilang Kelembaban

L/h	2,0
Pt/h	4,2

Sirkulasi Udara

Indoor	m ³ / min (ft ³ /min)	10,7 (380)
Outdoor	m ³ / min (ft ³ /min)	38,5 (1.360)

Tingkat Kebisingan

Indoor (H / L / Q-Lo)	dB-A	38/28/25
Outdoor (H)	dB-A	48

Dimensi

Tinggi	mm	290 [619]
	inci	11-7/16 [24-3/8]
Lebar	mm	779 [824]
	inci	30-11/16 [32-15/32]
Tebal	mm	209 [299]
	inci	8-1/4 [11-25/32]

Berat Bersih

Indoor	kg (lb)	8 (18)
Outdoor	kg (lb)	23 (51)

Diameter Pipa Pendingin

Sisi Cair	mm	Ø 6,35
	inci	1/4
Sisi Gas	mm	Ø 9,52
	inci	3/8

Sambungan Pipa

Chargeless Pipa Maksimum	m	7,5
Panjang Pipa Maksimum	m	20
Ketinggian Maksimum Pipa	m	15
Gas Pendingin Tambahan*	g/m	10

Pasokan Listrik

Indoor

> > > > >