



Standard Inverter - CS/CU-PU5XKJ

Model

(50Hz)	CS-PU5XKJ (CU-PU5XKJ)
--------	--------------------------

Kapasitas Pendinginan

(min-max)	kW	1,55 (0,77-1,91)
	Btu/h	5.300 (2.630-6.500)

EER (rated)

(min-max)	12,93 (11,82-13,84)
-----------	---------------------

EER (label)

Btu/hW	12,44
--------	-------

Tingkat Bintang

Star Level	Bintang 4
------------	-----------

Data kelistrikan

Voltase	V	220
Arus Daya	A	2,5
Daya Listrik (min-max)	W	410 (190-550)

Penghilang Kelembaban

L/h	1,0
Pt/h	2,1

Sirkulasi Udara

Indoor	m ³ / min (ft ³ /min)	8,1 (290)
Outdoor	m ³ / min (ft ³ /min)	26,7 (940)

Tingkat Kebisingan

Indoor (H / L / Q-Lo)	dB-A	35/25/22
Outdoor (H)	dB-A	47

Dimensi

Tinggi	mm	290 [490]
	inci	11-7/16 [19-9/32]
Lebar	mm	779 [650]
	inci	30-11/16 [25-19/32]
Tebal	mm	209 [230]
	inci	8-1/4 [9-1/16]

Berat Bersih

Indoor	kg (lb)	8 (18)
Outdoor	kg (lb)	18 (40)

Diameter Pipa Pendingin

Sisi Cair	mm	Ø 6,35
	inci	1/4
Sisi Gas	mm	Ø 9,52
	inci	3/8

Sambungan Pipa

Chargeless Pipa Maksimum	m	7,5
Panjang Pipa Maksimum	m	20
Ketinggian Maksimum Pipa	m	15
Gas Pendingin Tambahan*	g/m	10

Pasokan Listrik

Indoor

> > > > >